

VACULOAD 6Q

VACUUM UNIT



PRODUCT DESCRIPTION

The Vacuload 6Q vacuum system got its name for its 84 dBA sound reading at full vacuum. This powerful yet quiet vacuum system has become the standard in shipyards and factories. No hearing protection required!

RECOMMENDED USE

For use in industries including abrasive blasting and painting, ship cleaning, foundries, factories, mining, blast recovery, wastewater treatment and more.

SPECIFICATIONS

Skid mounted	4" x 8" rectangular tube frame, fork pockets and certified lifting cage
Power source	150 HP electric motor, 460 volt, 3 phase, hostile duty (Full Load amps 163, no load 48.8)
Sound attenuation 'quiet cube package'	Dual inlet and discharge silencers with sound attenuation enclosure
Vacuum air flow (blower)	Roots Dresser 2350 CFM capable of 27" Hg, 5 belt driven, with guard
Filtration system	Cyclonic separation. Baghouse - Teflon coated quick change filter bags with continuous reverse pulse air cleaning. High efficiency blower safety filter
Instrument panel (NEMA 4)	Soft start package, push-button on/off switch with indicator light, disconnect lever, air pulse on/off switch, material dump on/off switch

STANDARD EQUIPMENT

- Paint - one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator
- Emergency stop button
- 10" inspection manhole
- Flip top lid on baghouse

OPTIONS

- Slide gate discharge
- 16" manhole on bag house
- Auger in hopper (cone)
- Hydraulics (lift cylinder)
- HEPA Filtration
- Tool box
- Air compressor - 120 PSI
- Trailer-mounted to DOT standards



DIMENSIONS

