

# MEGAFLOW BULL HOSE



## APPLICATIONS

The MegaFlow air supply bull hose is designed for heavy duty large diameter pneumatic supply where severe conditions and higher working pressure ratings are needed. A long lasting hose designed for demanding applications in mining, construction, quarries and equipment rental.

## DESCRIPTION

This hose has a heavier construction and higher temperature capability to suit bull hose applications, with a working pressure of 69 Bar with a 4:1 safety factor. Whip checks are recommended and are readily available.

The wire braid improves kink-resistance, and also allows for a 600 PSI rating in ambient temperatures (when properly rated fittings are installed). Assemblies with bolted clamps (as shown) are available.

## FEATURES AND BENEFITS

- Super synthetic, oil resistant liner
- Durable UV resistant wrapped outer cover
- 300 psi pressure rated with 3:1 safety factor
- Non-fitted hose available in coils of 50 ft and 20 m
- Temperature range: -22°F (-30°C) to +158°F (+70°C)
- Nominal hose dimensions only – check with BlastOne for exact tolerances and suitable clamps

PART NUMBERS (NON-FITTED)		Outside diameter (inch) (mm)	
BH BULL38	MegaFlow Bull Hose 1-1/2" (38 mm) ID	2-1/8	54
BH BULL50	MegaFlow Bull Hose 2" (50 mm) ID	2-9/16	65
BH BULL75	MegaFlow Bull Hose 3" (76 mm) ID	3-5/8	92

PART NUMBERS (FITTED)	
BH BULL3850FCF	MegaFlow Bull Hose 1-1/2", 50 ft, fitted with 2 x 4-Claw Crowsfoot Couplings (USA only)
BH BULL3850FSP	MegaFlow Bull Hose 1-1/2", 50 ft, fitted with 2 x Spud Couplings (USA only)
BH BULL5050FCF	MegaFlow Bull Hose 2", 50 ft, fitted with 2 x 4-Claw Crowsfoot Couplings (USA only)
BH BULL5050FSP	MegaFlow Bull Hose 2", 50 ft, fitted with 2 x Spud Couplings (USA only)
BH BULL3820FSL	MegaFlow Bull Hose 38 mm, 20 m, fitted with 2 x Surelock Couplings (AU/NZ only)
BH BULL3820FSP	MegaFlow Bull Hose 38 mm, 20 m, fitted with 2 x Spud Couplings (AU/NZ only)
BH BULL5020FSL	MegaFlow Bull Hose 50 mm, 20 m, fitted with 2 x Surelock Couplings (AU/NZ only)
BH BULL5020FSP	MegaFlow Bull Hose 50 mm, 20 m, fitted with 2 x Spud Couplings (AU/NZ only)

**Note:** A hose restraint should be used at all times.